

RECEIVED
CENTRAL FAX CENTER
DEC 13 2006

25090A

AMENDMENT TO THE CLAIMS

1. (Currently amended) A glass-melting furnace comprising:
an elongated channel consisting of a charge end wall, a discharge end wall, two
side walls, a floor, and a roof, the elongated channel defining an upstream melting end, a
downstream fining end through which molten glass is discharged, and a roof; the
upstream end being positioned upstream of the downstream end in the glass-melting
furnace;
a charger supplying glass-forming material to the upstream end of the glass-
melting furnace;
at least one burner supplying heat to the glass-forming material at the upstream
end of the glass-melting furnace; and
an exhaust positioned at the downstream end of the glass-melting furnace and in
communication with the downstream end of the furnace so that combustion gases in the
glass-melting furnace are exhausted only from the exhaust at the downstream end of the
glass-melting furnace, the exhaust further being positioned downstream of the at least one
burner.

2. (Previously presented) The glass-melting furnace of claim 1 in which
the at least one burner is mounted through the roof of the glass-melting furnace.

3. (Original) The glass-melting furnace of claim 1 in which the at least one
burner is a plurality of burners.

4. (Original) The glass-melting furnace of claim 3 in which more than 50
percent of the burners are positioned upstream of the exhaust.

25090A

5. (Original) The glass-melting furnace of claim 4 in which all of the burners are positioned upstream of the exhaust.
6. (Original) The glass-melting furnace of claim 1 in which the exhaust is an exhaust stack.
7. (Original) The glass-melting furnace of claim 1 in which the exhaust is a plurality of exhaust stacks.
8. (Previously presented) The glass-melting furnace of claim 1 in which the exhaust is disposed at a discharge end wall of the glass-melting furnace.
9. (Previously presented) The glass-melting furnace of claim 1 in which the exhaust is disposed at a sidewall of the glass-melting furnace.
10. (Previously presented) The glass-melting furnace of claim 1 in which the at least one burner is a plurality of burners mounted through the roof of the glass-melting furnace, all of the burners are positioned upstream of the exhaust outlets, and the exhaust comprises at least two exhaust outlets.
11. (Original) The glass-melting furnace of claim 10 in which the exhaust outlets are a plurality of exhaust stacks.
12. (Currently amended) A glass-melting furnace comprising:
an elongated channel consisting of a charge end wall, a discharge end wall, two side walls, a floor, and a roof, the elongated channel defining an upstream melting end having a charge end wall and a downstream fining end having a discharge end wall through which molten glass is discharged, the upstream end being positioned upstream of the downstream end in the glass-melting furnace;

25090A

an exhaust in communication with the glass-melting furnace, the exhaust having a centerline that is positioned at least about 70 percent of the distance from the charge end wall of the glass-melting furnace to the discharge end wall of the glass-melting furnace so that combustion gases in the glass-melting furnace are exhausted only from the exhaust having its centerline positioned at least about 70 percent of the distance from the charge end wall of the glass-melting furnace to the discharge end wall of the glass-melting furnace.

13. (Previously presented) The glass-melting furnace of claim 11 in which the exhaust centerline is positioned at least about 80 percent of the distance from the charge end wall of the glass-melting furnace to the discharge end wall of the glass-melting furnace.

14. (Previously presented) The glass-melting furnace of claim 12 wherein the glass-melting furnace comprises two sidewalls and two exhausts, each exhaust being separated laterally from the sidewalls.

15. (Currently amended) In a glass-melting furnace having an elongated channel consisting of a charge end wall, a discharge end wall, two side walls, a floor, and a roof, the elongated channel defining an upstream melting end with a charge end wall and a downstream fining end ~~with a discharge end wall~~ through which molted glass is discharged, the upstream end being positioned upstream of the downstream end, the improvement comprising: an exhaust in communication with the glass-melting furnace at the downstream end of the glass-melting furnace so that combustion gases in the glass-melting furnace are exhausted only from the exhaust in communication with the glass-melting furnace at the downstream end.

16. (Original) The glass-melting furnace of claim 15 wherein the exhaust is disposed at the discharge end wall.

25090A

17. (Original) The glass-melting furnace of claim 15 wherein the exhaust comprises an exhaust stack.

18. (Original) The glass-melting furnace of claim 15 wherein the exhaust comprises a plurality of exhaust stacks.

19-26. (Cancelled)

27. (Currently amended) A glass-melting furnace comprising:
an elongated channel consisting of a charge end wall, a discharge end wall, two side walls, a floor, and a roof, the elongated channel defining an upstream melting end and a downstream fining end through which molten glass is discharged;
a charger supplying glass-forming material to the upstream end of the glass-melting furnace; and
at least one exhaust at the downstream end of the glass-melting furnace, wherein combustion gases in the glass-melting furnace are exhausted only from the at least one exhaust.

28. (Previously presented) The glass-melting furnace of claim 27 in which the at least one exhaust has a centerline that is positioned at least about 70 percent of the distance from the upstream end to the downstream end of the glass-melting furnace.

29. (Currently amended) A glass-melting furnace comprising:
an elongated channel consisting of a charge end wall, a discharge end wall, two side walls, a floor, and a roof, the elongated channel defining an upstream melting end and a downstream fining end through which molten glass is discharged;
a charger supplying glass-forming material to the upstream end of the glass-melting furnace;

25090A

at least one burner supplying heat to the glass-forming material at the upstream end of the glass-melting furnace; and

one or more exhausts positioned only at the downstream end of the glass-melting furnace and in communication with the downstream end of the glass-melting furnace so that combustion gases in the furnace are exhausted only from the downstream end of the glass-melting furnace.

30. (Previously presented) The glass-melting furnace of claim 29 in which the one or more exhausts have centerlines that are positioned at least about 70 percent of the distance from the upstream end to the downstream end of the glass-melting furnace.

31. (Currently amended) A glass-melting furnace comprising:
an elongated channel consisting of a charge end wall, a discharge end wall, two side walls, a floor, and a roof, the elongated channel defining a melting zone first half, and a fining zone second half through which molten glass is discharged;
a charger supplying glass-forming material to a charge end of the first half of the glass-melting furnace;

at least one burner supplying heat to the glass-forming material in the first half of the glass-melting furnace; and

at least one exhaust positioned at the second half of the glass-melting furnace and in communication with the second half of the glass-melting furnace with no exhaust positioned at the first half of the glass-melting furnace so that combustion gases in the glass-melting furnace are exhausted only from the second half of the glass-melting furnace.

32. (Previously presented) The glass-melting furnace of claim 31 wherein the first half defines a charge end and the second half defines a discharge end, the at least one exhaust having a centerline that is positioned at least about 70 percent of the distance from the upstream end to the downstream end of the glass-melting furnace.

25090A

33. (Cancelled)

34. (Previously Presented) The glass-melting furnace of claim 1 further at least one downstream burner supplying heat to the downstream fining end.

35. (Previously Presented) The glass-melting furnace of claim 34 in which the downstream burner is mounted in the roof.

36. (Previously Presented) The glass-melting furnace of claim 35 in which at least one upstream burner is mounted at an angle of up to about 20 degrees to the vertical.

37. (Currently Amended) The glass-melting furnace of claim ~~37~~ 36 in which the downstream burner is mounted at an angle of up to about 20 degrees to the vertical.